



KAI

Casual all-around hat made of recycled polyester and elastane. It features a mid visor, recycled dry-tech sweatband and a HQ hook&loop closure with elastic and buckle.

Technical details

Closure: Hook-and-loop closure with plastic loop and elastic string

Eyelets: 6 Sewn eyelets on crown areas

Lining: Recycled lamination on front panels

Main fabric weight: 195 gsm

Packing: 24 x 144 pcs

Product weight kg: 0,070

Size: One size fits all

Washing: WATER RESISTANT - PFC FREE / Anti - Uv Treatment

Customs code: 6505.00.30

Composition: 97% polyester 3% elastane

Fabric: Main Fabric: 97% Recycled Polyester 3% Elastane

Made in: China


Others: Button

Panels: 6 Panels


Shape: Soft crown


Visor: 6 rows / Mid Visor / Retraze Recycled Visor


Circumference: 58.5 cm


 **Recycled dry-tech sweatband**
Elastic sweatband, made by recycled material, enhanced by a quick dry function and antibacterial properties.

 **Uv protection**
Fabrics that offer a 50+ protection from the ultraviolet rays of the sun.

 **Water resistant - pfc free**
WR-PFC free it's our water-resistant treatment that keeps our caps dry, without environmental harmful components.

 **Recycled polyester**
Fiber made from polymers obtained by recycling plastic bottles.

 **Retraze recycled visor**
Internal visor made of 100% recycled plastic (PE), made in partnership with ReTraze®. Starting with the 2024 productions.

 **Soft crown**
Soft crown for a pleasure feeling.

Where to customize (Centimeters)

	Front	Back	Closure	Right	Left
Print	-	-	6 x 1,2	6 x 5	6 x 5
Embroidery	12 x 6	8 x 3,5	3 x 1	10 x 6	10 x 6
Heat transfer	-	-	-	6 x 4	6 x 4

Washing instruction



Hand wash/ do not bleach/ do not dry by tumble dryers/ dry flat/ do not iron/ do not dry clean/ do not professional wet clean

Color variants (TPX / Pantone)

WHITE

HAT: 11-0601 / WHITE



DARK-GREY

HAT: 19-3906 / COOL-GRAY-11-C



BLACK

HAT: 19-4005 / BLACK-C



NAVY

HAT: 19-3920 / 533-C



SAGE

HAT: 16-5907 / 4185-C

